

	Toshiba e-STUDIO3015AC	Toshiba e-STUDIO4515AC	Toshiba e-STUDIO6516AC
MODEL INFORMATION			
Manufacturer	Toshiba	Toshiba	Toshiba
Model	e-STUDIO3015AC	e-STUDIO4515AC	e-STUDIO6516AC
Product Type	Full-color copier, MF	Full-color copier, MF	Full-color copier, MF
Product Status	Current	Current	Current
Introduction Date	09/01/2018	09/01/2018	12/01/2018
Discontinued Date	Info not avail	Info not avail	Info not avail
Market Segment	2	4	5
OEM	Toshiba (China)	Toshiba (China)	Toshiba (China)
Maximum Monthly Duty Cycle	180,000 black/90,000 color impressions	210,000 black/105,000 color impressions	540,000 impressions
Recommended Monthly Volume	N/A	N/A	N/A
MSRP/Street Price	\$17,580.00 / None	\$27,196.00 / None	\$42,056.00 / None
Dimensions (HxWxD)	31" x 23" x 25.2"	31" x 23" x 25.2"	48.3" x 37.6" x 27.5"
Weight	172 lbs	172 lbs	470 lbs
GENERAL SPECIFICATIONS			
Control Panel	10.1" color touchscreen	10.1" color touchscreen	10.1" color touchscreen
Copy Speed (Ltr/Lgl/Ldgr)	30 cpm color/30 cpm black / Info not avail / Info not avail	45 cpm color/45 cpm black / Info not avail / Info not avail	65 cpm color/75 cpm black / Info not avail / Info not avail
First Copy Out Time	7.8 sec color/5.9 sec black	5.7 sec color/4.4 sec black	6.4 sec color/4.5 sec black
Warm-up Time	20 sec	20 sec	20 sec
Paper Sources (Std/Max)	Dual drawer	Dual drawer	Four drawer
Standard Paper Capacity	550/550 sheets	550/550 sheets	540/540/540/540 sheets
Paper Weights	16-lb bond to 140-lb index	16-lb bond to 140-lb index	16-lb bond to 140-lb index
Bypass/Paper Weights	100-sheet / 14-lb bond to 100-lb cover	100-sheet / 14-lb bond to 100-lb cover	120-sheet / 16-lb bond to 110-lb cover
Maximum Paper Sources	5	5	6
Maximum Paper Capacity	3,200 sheets	3,200 sheets	4,780 sheets
Maximum Original Size	11 x 17	11 x 17	11 x 17
Output Size (Minimum/Maximum)	3.9 x 5.8 / 12 x 18	3.9 x 5.8 / 12 x 18	3.9 x 5.8 / 13 x 19
Copy Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
System Memory (Standard/Maximum)	4-GB RAM, 320-GB HD / 4-GB RAM, 320-GB HD	4-GB RAM, 320-GB HD / 4-GB RAM, 320-GB HD	4-GB RAM, 320-GB HD / 4-GB RAM, 320-GB HD
Duplex	Auto (1:2,2:2,2:1)	Auto (1:2,2:2,2:1)	Auto (1:2,2:2,2:1)
Duplex Capacity/Paper Sizes	Info not avail / 5.8 x 8.3 to 12 x 18	Info not avail / 5.8 x 8.3 to 12 x 18	Info not avail / 5.8 x 8.3 to 13 x 19
Document Feeder	Opt RADF and DSPF	Opt RADF and DSPF	Std DSPF
Document Feeder Capacity	100 orig, 300 orig	100 orig, 300 orig	300 orig
Paper Weights	9.3 to 41.8 lbs, 9.3-lb bond to 110-lb index	9.3 to 41.8 lbs, 9.3-lb bond to 110-lb index	9.3-lb bond to 110-lb index
Finisher	Opt finishers	Opt finishers	Opt finishers
Tray/Stapling/Position(s)	600, 2,250, 3,250 / 50 / 3	600, 2,250, 3,250 / 50 / 3	3,250 / 50 / N/A
Hard Drive	4-GB RAM, 320-GB HD / 4-GB RAM, 320-GB HD	4-GB RAM, 320-GB HD / 4-GB RAM, 320-GB HD	4-GB RAM, 320-GB HD / 4-GB RAM, 320-GB HD

TOSHIBA

	Toshiba e-STUDIO3015AC	Toshiba e-STUDIO4515AC	Toshiba e-STUDIO6516AC
Additional Features	Opt RADF (reversing automatic document feeder) or DSPF (duplex single pass feeder); opt inner finisher has two trays (100/500 sheets); opt multi-position finisher has a 2,000-sheet tray plus 250-sheet stationary tray; opt saddle-stitch finisher handles 3,250 sheets and features V-folding and saddle-stitching of up to 15 sheets (60-page booklets); opt hole punch available for each finisher; opt paper feed-pedestal adds one 550-sheet drawer; an additional opt 550-sheet drawer or opt envelope feeder cassette can be added to the paper-feed pedestal; opt 2,000-sheet LCT handles letter/A4-sized paper; banner-sized paper can be handled via the bypass tray	Opt RADF (reversing automatic document feeder) or DSPF (duplex single pass feeder); opt inner finisher has two trays (100/500 sheets); opt multi-position finisher has a 2,000-sheet tray plus 250-sheet stationary tray; opt saddle-stitch finisher handles 3,250 sheets and features V-folding and saddle-stitching of up to 15 sheets (60-page booklets); opt hole punch available for each finisher; opt paper feed-pedestal adds one 550-sheet drawer; an additional opt 550-sheet drawer or opt envelope feeder cassette can be added to the paper-feed pedestal; opt 2,000-sheet LCT handles letter/A4-sized paper; banner-sized paper can be handled via the bypass tray	Opt multi-position finisher has a 3,000-sheet finishing tray and 250-sheet stationary tray; opt saddle-stitch finisher features a 3,000-sheet finishing tray, 250-sheet stationary tray, V-folding and saddle-stitching of up to 15 sheets (60-page booklets); opt hole punch available for either finisher; opt 2,500-sheet LCT handles letter/A4-sized paper; banner-sized paper can be handled via the bypass tray; duplexer handles paper weights up to 140-lb index/256 gsm
MULTIFUNCTION FEATURES			
Copier	Std	Std	Std
Printer			
Standalone Printer	Std	Std	Std
Network Printer	Std	Std	Std
Scanner	Std	Std	Std
Fax	Opt	Opt	Opt
Internet Fax	Std	Std	Opt
Network Fax	Opt	Opt	Opt
PC Fax	Opt	Opt	Opt
PRINTER SPECIFICATIONS			
Speed	30 ppm color/30 ppm black	45 ppm color/45 ppm black	65 ppm color/75 ppm black
Maximum Print Area	Info not avail	Info not avail	Info not avail
Print Resolution	1200 x 1200 dpi	1200 x 1200 dpi	1200 x 1200 dpi
Paper Type	3.9 x 5.8 / 12 x 18	3.9 x 5.8 / 12 x 18	3.9 x 5.8 / 13 x 19
Std/Max Printer Memory	Info not avail	Info not avail	Info not avail
Standard Controller	Toshiba e-BRIDGE Next	Toshiba e-BRIDGE Next	Toshiba e-BRIDGE Next
Processor/Bits/MHz	Intel Atom E3825 Dual Core / N/A / 1.33 GHz	Intel Atom E3825 Dual Core / N/A / 1.33 GHz	Intel Atom Dual Core / N/A / 1.75 GHz
PDL/PCL	PCL 5e/c/6, PostScript 3, XPS	PCL 5e/c/6, PostScript 3, XPS	PCL 5e/c/6, PostScript 3, XPS
Controller Features	Secure, proof and scheduled print; secure pattern printing; overlay, tab, poster, cover and tandem print; insert page; do not print white page; watermarks; supports banner printing up to 12" x 47"/305 mm x 1200 mm; print to e-Filing; universal print driver	Secure, proof and scheduled print; secure pattern printing; overlay, tab, poster, cover and tandem print; insert page; do not print white page; watermarks; supports banner printing up to 12" x 47"/305 mm x 1200 mm; print to e-Filing; universal print driver	Secure, proof and scheduled print; secure pattern printing; overlay, tab, poster, cover and tandem print; insert page; do not print white page; watermarks; supports banner printing up to 12.3" x 47"/313.3 mm x 1200 mm; print to e-Filing
SCANNER SPECIFICATIONS			
Connection Type	Info not avail	Info not avail	Info not avail
Technology/Speed	CCD / 73 ipm color, 73 ipm black or 120 ipm color, 120 ipm black	CCD / 73 ipm color, 73 ipm black or 120 ipm color, 120 ipm black	CCD / 120 ipm color, 120 ipm black
Maximum Resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
TWAIN Compatible	Yes	Yes	Yes
Scan Destinations			
E-mail	Yes	Yes	Yes
I-fax	Yes	Yes	Yes
FTP	Yes	Yes	Yes
SMB	Yes	Yes	Yes
HDD	Yes	Yes	Yes
URL	Yes	Yes	Yes
LDAP Support	Yes	Yes	Yes
File Formats	DOCX, JPEG, PDF, PDF/A, compact PDF, searchable PDF, secure PDF, PPTX, TIFF, XLSX, XPS	DOCX, JPEG, PDF, PDF/A, compact PDF, searchable PDF, secure PDF, PPTX, TIFF, XLSX, XPS	DOCX, JPEG, PDF, compact PDF, searchable PDF, secure PDF, PPTX, TIFF, XLSX, XPS

TOSHIBA

	Toshiba e-STUDIO3015AC	Toshiba e-STUDIO4515AC	Toshiba e-STUDIO6516AC
Scanner Features	Thumbnail scan preview; scan to cloud (Dropbox, Google Drive, Microsoft Exchange, OneDrive, SharePoint); scan to box (e-Filing); scan speeds based on 300 dpi	Thumbnail scan preview; scan to cloud (Dropbox, Google Drive, Microsoft Exchange, OneDrive, SharePoint); scan to box (e-Filing); scan speeds based on 300 dpi	Color scanning; scan to box (e-Filing); scan speeds based on 300 dpi
SECURITY SPECIFICATIONS			
Network User Authentication	Yes	Yes	Yes
IP Address Filtering	Yes	Yes	Yes
MAC Address Filtering	Yes	Yes	Yes
HDD Overwrite	Std	Std	Opt
Number of Overwrites	15	15	15
HDD Encryption	Std	Std	Std
Encrypted Secure Print	Yes	Yes	Yes
Encrypted PDF Mode (Encrypted Scanning)	Std	Std	Std
IPsec	Opt	Opt	Opt
Secure Sockets Layer (SSL)	Yes	Yes	Yes
SNMPv3	Yes	Yes	Yes
Transport Layer Security (TLS)	Yes	Yes	Yes
Secure Print	Yes	Yes	Yes
Security Features	Std self-encrypting HDD with automatic drive invalidation and data overwrite provides 256-bit AES encryption; opt FIPS 140-2 validated self-encrypting HDD; opt hardcopy security printing provides unauthorized copy control; opt e-BRIDGE SmartCard card reader limits unauthorized access to device; IPv6; 802.1x authentication; port filtering	Std self-encrypting HDD with automatic drive invalidation and data overwrite provides 256-bit AES encryption; opt FIPS 140-2 validated self-encrypting HDD; opt hardcopy security printing provides unauthorized copy control; opt e-BRIDGE SmartCard card reader limits unauthorized access to device; IPv6; 802.1x authentication; port filtering	Std self-encrypting HDD provides 256-bit AES encryption; opt data overwrite kit required for overwrite capability; opt hardcopy security printing provides unauthorized copy control; opt e-BRIDGE SmartCard card reader limits unauthorized access to device; IPv6; 802.1x authentication; port filtering; opt FIPS 140-2 Validated self-encrypting HDD; HCD-PP certified (ISO/IEC15408)
FAX SPECIFICATIONS			
Compression Method	MH/MR/MMR/JBIG	MH/MR/MMR/JBIG	MH/MR/MMR/JBIG
Dual Lines	Opt	Opt	Opt
Fax Features	1-GB (HDD) transmission/reception memory plus HD backup memory; incoming fax routing to shared folder, e-mail or e-Filing; approximately 3 seconds per page transmission speed	1-GB (HDD) transmission/reception memory plus HD backup memory; incoming fax routing to shared folder, e-mail or e-Filing; approximately 3 seconds per page transmission speed	1-GB (HDD) transmission/reception memory plus HD backup memory; incoming fax routing to shared folder, e-mail or e-Filing; approximately 3 seconds per page transmission speed
CONNECTIVITY			
Operating System Support	Win Vista, Server 2008, 7, Server 2012, 8, 8.1, 10, Server 2016, Mac OS X 10.7.4-10.13, Citrix, Linux, Novell Netware, UNIX	Win Vista, Server 2008, 7, Server 2012, 8, 8.1, 10, Server 2016, Mac OS X 10.7.4-10.13, Citrix, Linux, Novell Netware, UNIX	Win Server 2008, 7, Server 2012, 8.1, 10, Server 2016, Mac OS X 10.7.4-10.13, Citrix, Linux, Novell Netware, UNIX
USB Interface	Std 2.0, std 2.0 (host)	Std 2.0, std 2.0 (host)	Std 2.0, std 2.0 (host)
PC Fax/Print/Scan	Info not avail	Info not avail	Info not avail
Network Interface	Std Ethernet, opt wireless	Std Ethernet, opt wireless	Std Ethernet, opt wireless
Interface Type	10/100/1000BaseTX, 802.11b/g/n, Bluetooth	10/100/1000BaseTX, 802.11b/g/n, Bluetooth	10/100/1000BaseTX, 802.11b/g/n, Bluetooth
LAN Fax/Print/Scan	Info not avail	Info not avail	Info not avail
POWER AND ENERGY			
Power Requirements	120 V, 12 A	120 V, 12 A	120 V, 16 A
Energy Star Compliant	Yes	Yes	Yes

TOSHIBA

e-STUDIO™ 3515AC series

- > Color Multifunction Printer
- > Up to 35 PPM
- > Medium Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Customizable UI



e-STUDIO™ 2515Ac/3015Ac/3515Ac

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	25/30/35 PPM (LT)
First Copy Out	Color: 7.8/7.8/7.8 Seconds Monochrome: 5.9/5.9/5.9 Seconds
Warm-Up Time	Approx. 20 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 3,200 Sheets
Original Feed	Optional 300-Sheet DSDf or 100-Sheet RADf
Scan Speed & Weights	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color), Simplex: 9.3-110 lb Bond, Duplex: 9.3-110 lb Bond RADf Scan: Up to 73 IPM (Monochrome or Color), Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond
Max. Original Size	LD
Paper Feed Sizes	Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 550 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 100 Sheets-14 lb Bond-100 lb Cover Opt. 550-Sheet Paper Feed Pedestal-16 lb Bond-140 lb Index Opt. 550 Sheets Drawer for PFP-16 lb Bond-140 lb Index Opt. Envelope Cassette for PFP-16 lb Bond-140 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17 lb-28 lb Bond Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Paper Weights	
Duplex	
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 75K/90K/105K Month (Color: 100%) Max. 150K/180K/210K Month (Monochrome: 100%) Approx. 172 lb
Weight	23" (W) x 25.2" (D) x 31" (H)
Approx. Dimensions	
CMYK Toner Yield	CMY: 33.6K, K: 38.4K @ 5%
Power Source	120 Volts, 50/60 Hz, 12 Amps
Power Consumption	Maximum 1.5kW (120V)
CPU	Intel Atom™ 1.33 GHz (Dual-Core)
Memory	4GB
Hard Disk Drive	320GB Self-Encrypting Drive

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	25/30/35 Pages Per Minute (LT)
Print Resolution	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7, 8.1, 10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13 RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Interface	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Wireless Device	
Device Management	TopAccess, eFMS 6.30 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/ Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, NFC Authentication
*Conformance with HCD-PPv1.0 in High Security Mode.
ENERGY STAR® (V2.0), EPEAT Gold, Californian Proposition 65
WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Stds. Certification

Scan Specifications

Scan Speed	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADf Scan: Up to 73 IPM (Monochrome or Color)
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options		Accessory Tray	GR1330
DSDf	MR4000	Panel 10-Key Option	GR1340
RADf	MR3031	Card Reader Holder	GR1320
Platen Cover	KA5005PC	USB Hub	GR1310
Additional Paper Options		Meta Scan Enabler	GS1010
Paper Feed Pedestal	KD1058	IPsec Enabler	GP1080
Drawer Module	MY1048	Unicode Font Enabler	GS1007
Envelope Cassette Option	MY1049	Embedded OCR Enabler	
Large Capacity Feeder	KD1059LT	Per Seat License	GS1080
Finishing Options		Multi-Station Print Enabler	
Inner Finisher	MJ1042	Per Seat License	GS1090
50-Sheet Staple Finisher	MJ1109	SharePoint® Connector	GB1440
Saddle-Stitch Finisher	MJ1110	Exchange Connector	GB1450
Hole Punch Unit for MJ1042	MJ6011	Google Docs™ Connector	GB1540
Hole Punch Unit for MJ1109/MJ1110	MJ6105	Hardcopy Security Printing	GP1190A
Bridge Kit	KN5005	FIPS HDD	GE1230
Job Separator	MJ5015	Monotype Font Option	GB2050
Connectivity/Security Options		Miscellaneous Options	
FAX Unit/2nd Line for FAX Unit	GD1370N	Stand	STAND5005
Wireless LAN/Bluetooth	GN4020	Accessible Arm	KK2550
Hardcopy Security Printing	GP1190A	Work Tray	KK5005
Bluetooth Keyboard	GR9000	Manual Pocket	KK5008
		Harness Kit for Coin Controller	GQ1280

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Web Site

www.business.toshiba.com

TOSHIBA

e-STUDIO™ 5015AC series

- > Color Multifunction Printer
- > Up to 50 PPM
- > Medium/Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Customizable UI



e-STUDIO™ 4515Ac/5015Ac

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/Laser Printing/ Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	45/50 PPM (LT)
First Copy Out	Color: 5.7/5.7 Seconds Monochrome: 4.4/4.4 Seconds
Warm-Up Time	Approx. 20 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 3,200 Sheets
Original Feed	Optional 300-Sheet DSD/ or 100-Sheet RADF
Scan Speed & Weights	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color), Simplex: 9.3-110 lb Bond, Duplex: 9.3-110 lb Bond RADF Scan: Up to 73 IPM (Monochrome or Color), Simplex: 9.3-41.8 lb Bond, Duplex: 13.3-41.8 lb Bond
Max. Original Size	LD
Paper Feed Sizes	Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Standard: 550 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 100 Sheets-14 lb Bond-100 lb Cover Opt. 550-Sheet Paper Feed Pedestal-16 lb Bond-140 lb Index Opt. 550 Sheets Drawer for PFP-16 lb Bond-140 lb Index Opt. Envelope Cassette for PFP-16 lb Bond-140 lb Index Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-17 lb-28 lb Bond Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Paper Weights	
Duplex	
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 105K/105K Month (Color: 100%) Max. 210K/210K Month (Monochrome: 100%) Approx. 172 lb
Weight	23" (W) x 25.2" (D) x 31" (H)
Approx. Dimensions	
CMYK Toner Yield	CMY: 33.6K, K: 38.4K @ 5%
Power Source	120 Volts, 50/60 Hz, 12 Amps
Power Consumption	Maximum 1.5kW (120V)
CPU	Intel Atom™ 1.33 GHz (Dual-Core)
Memory	4GB
Hard Disk Drive	320GB Self-Encrypting Drive

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	45/50 Pages Per Minute (LT)
Print Resolution	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7, 8.1, 10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess, eFMS 6.30 (e-BRIDGE Fleet Management Software)
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/ Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, NFC Authentication
*Conformance with HCD-PPv1.0 in High Security Mode.
ENERGY STAR® (V2.0), EPEAT Gold, Californian Proposition 65
WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Stds. Certification

Scan Specifications

Scan Speed	DSD/ Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADF Scan: Up to 73 IPM (Monochrome or Color)
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Platen & Document Feeder Options		Accessory Tray	GR1330
DSD/	MR4000	Panel 10-Key Option	GR1340
RADF	MR3031	Card Reader Holder	GR1320
Platen Cover	KA5005PC	USB Hub	GR1310
Additional Paper Options		Meta Scan Enabler	GS1010
Paper Feed Pedestal	KD1058	IPsec Enabler	GP1080
Drawer Module	MY1048	Unicode Font Enabler	GS1007
Envelope Cassette Option	MY1049	Embedded OCR Enabler	
Large Capacity Feeder	KD1059LT	Per Seat License	GS1080
Finishing Options		Multi-Station Print Enabler	
Inner Finisher	MJ1042	Per Seat License	GS1090
50-Sheet Staple Finisher	MJ1109	SharePoint® Connector	GB1440
Saddle-Stitch Finisher	MJ1110	Exchange Connector	GB1450
Hole Punch Unit for MJ1042	MJ6011	Google Docs™ Connector	GB1540
Hole Punch Unit for MJ1109/MJ1110	MJ6105	Hardcopy Security Printing	GP1190A
Bridge Kit	KN5005	FIPS HDD	GE1230
Job Separator	MJ5015	Monotype Font Option	GB2050
Connectivity/Security Options		Miscellaneous Options	
FAX Unit/2nd Line for FAX Unit	GD1370N	Stand	STAND5005
Wireless LAN/Bluetooth	GN4020	Accessible Arm	KK2550
Hardcopy Security Printing	GP1190A	Work Tray	KK5005
Bluetooth Keyboard	GR9000	Manual Pocket	KK5008
		Harness Kit for Coin Controller	QQ1280

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Web Site

www.business.toshiba.com

TOSHIBA

e-STUDIO™ 7516AC series

- > Color Multifunction Printer
- > Up to 75 PPM Color
- > Up to 85 PPM Black & White
- > Large Workgroup
- > Copy, Print, Scan, Fax
- > Secure MFP
- > Customizable UI



e-STUDIO™ 5516AC/6516AC/7516AC

Main Specifications

Copy System	Indirect Electrostatic Photographic Method/OPC/Laser Printing/Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	Color: 55/65/75 PPM (LT), Monochrome: 65/75/85 PPM (LT)
First Copy Out	Color: 6.4/6.4/5.4, Monochrome: 5.2/4.5/4.1 Seconds
Warm-Up Time	Approx. 20 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope
Multiple Copying	Up to 9,999 Copies
Paper Capacity	4-Drawer: 2,280 Sheets/Max. 4,780 Sheets Tandem Drawer: Standard 3,520 Sheets/Max. 6,020 Sheets
Original Feed	Standard 300-Sheet DSDF
Scan Speed & Weights	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color), Simplex: 9.3-110 lb Index, Duplex: 9.3-110 lb Index
Max. Original Size	LD
Paper Feed Sizes	Drawers: 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF 1,160 x 2 LT-Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner Opt. 2,500-Sheet Ext. LCF LT-Only
Paper Weights	4-Drawer: Standard 540 Sheets x 4-16 lb Bond-140 lb Index Tandem LCF 1,160 Sheets x 2-16 lb Bond-140 lb Index Plus 540 Sheets x 2-16 lb Bond-140 lb Index Stack Feed Bypass: 120 Sheets-16 lb Bond-110 lb Cover Opt. 2,500-Sheet Ext. LCF LT-Only -16 lb Bond-140 lb Index Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Duplex	Standard Automatic Duplex Unit (16 lb Bond-140 lb Index)
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 480K/540K/600K Month (Color: 100%)
Weight	Approx. 470 lb
Approx. Dimensions	37.6" (W) x 27.5" (D) x 48.3" (H)
Toner Yield	CMY: 39,200, K: 106,600 @ 5%
Power Source	120 Volts, 50/60 Hz, 16 Amps
Power Consumption	Maximum 2.0kW (120V)
CPU	Intel Atom™ 1.75 GHz (Dual-Core)
Memory	4GB
Hard Disk Drive	320GB Self-Encrypting Drive

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Speed	Color: 55/65/75 PPM (LT), Monochrome: 65/75/85 PPM (LT)
Print Resolution	600 x 600 dpi (8 bit), 1,200 x 1,200 dpi (Color/2 bit) or 3,600 x 1,200 dpi (BW/with Smoothing) PS3 Only
Operating Systems	Windows Server® 2008 R2, R2 SP1, 2008/SP2, Windows® 7, 8.1, 10, Windows Server® 2012/R2, Windows Server® 2016, Macintosh® (macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, macOS 10.12, 10.13), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh® Environments
Printing Protocols	SMB, LPR/LPD, IPP (Ver.2.0) w/Authentication, AppleTalk® PAP or, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/ iPrint, WS Print, FTP
Print Drivers	Windows Server® 2008 SP2 (32-bit, 64-bit) Windows Server® 2008 R2 SP1 (64-bit), Windows® 7 SP1 (32-bit, 64-bit), Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016, Windows® 10 (32-bit, 64-bit), macOS X 10.7.4, 10.8, 10.9, 10.10, 10.11, macOS 10.12, 10.13
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional
Wireless Device	802.11b/g/n, Wireless LAN, Optional Bluetooth
Device Management	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Account Control	TopAccess, EFMS 6.3 (e-BRIDGE Fleet Management Software)
Accessibility Features	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout and Audible Beep Message Alerts



Security Features

User Authentication, On-Board Data Scramble Function, SCEP, Disable e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, NFC Authentication *Conformance with HCD-PPv1.0 in High Security Mode.

Environmental Stds. Certification

ENERGY STAR® (V2.0), EPEAT Gold
WHQL (Windows® 7, 8, 8.1, 10, 2008 R2, 2012, 2012 R2), Novell®, Citrix®, SAP, AirPrint®, Mopria®

Scan Specifications

Scan Speed	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color)
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.) Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF (Opt.), XPS-Multi/Single Page, DOCX (Opt.), XLSX (Opt.), PPTX (Opt.)
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Additional Paper Options			
Large Capacity Feeder	MP2502	IPsec Enabler	GP1080
		Unicode Font Enabler	GS1007
		FIPS 140-2 Validated SED	GE1230
Finishing Options		Embedded OCR Enabler	
50-Sheet Staple Finisher	MJ1111B	Per Seat License	GS1080
Saddle-Stitch Finisher	MJ1112B	Multi-Station Print Enabler	
Hole Punch Unit for MJ1111B/MJ1112B	MJ6106N	Per Seat License	GS1090
Side Exit Tray	KA6551	SharePoint® Connector	GB1440
Finisher Guide Rail	KN1103	Exchange Connector	GB1450
		Google Docs™ Connector	GB1540
Connectivity/Security Options		Miscellaneous Options	
FAX Unit/2nd Line for FAX Unit	GD1370N	Accessible Arm	KK2550
Wireless LAN/Bluetooth	GN4020	Harness Kit for Coin Controller	GQ1280
Bluetooth Keyboard	GR9000	Manual Pocket	KK5008
Accessory Tray	GR1330		
Panel 10-Key Option	GR1340		
Card Reader Holder	GR1320		
Meta Scan Enabler	GS1010		

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Web Site

www.business.toshiba.com